



I'm not robot



**Open**

# Bosch serie 4 dishwasher manual



Bosch sms46gi01a serie 4 freestanding dishwasher manual. Bosch serie 4 dishwasher installation manual. Bosch serie 4 smv46jx01g fully integrated dishwasher manual. Bosch serie 4 slimline dishwasher manual. Bosch smu46gs01a serie 4 under bench dishwasher manual. Bosch dishwasher serie 4 super silence 46db manual. Bosch serie 4 dishwasher manual pdf. Bosch serie 4 silence plus dishwasher manual.

Safety instructions en 7 Childproof lock (door lock) \* DoorlockThe child-proof lock (door lock) protects children from potential hazards which the dishwasher poses. .46 Removal . Changing the blades is easy and effortless, and the updated model is quieter than its predecessors. ■ Install built-under or integratable appliances only under continuous worktops which have been screwed to adjacent cupboards to ensure stability. Drainage connection 1. Fault Reason Remedial action \* depending on the configuration of your specific dishwasher Fault, what to do? Dependsondomesticinstallation, as no appliance fault. If you do not require the etagere, it can be folded up. \* depending on the features of your dishwasher Note: Utensils must not be placed above the tablet collecting tray 1B. Notes ■ Only clean the appliance with special detergents/appliance cleaners which are suitable for use with dishwashers. 23 Programme selection . In the display window you will see -. Each time the button is pressed, the set value increases by one level; when it reaches the value +: the display jumps back to +: (Off), on 35 Fault code +:f... is lit. When using Multitabs, select setting 0. +:f The appliance switches off after 120 minutes. Do not prerinse utensils. See rating plate for required fusing 9. Fill the dispenser with water (required only when switching on the appliance for the first time). The estimated programme duration appears in the display window ). Please ask your dealer or inquire at your local authority about current means of disposal. 17 Folding spikes. If you're in the market to purchase some new tools, you'll want to consider the reputation of the company. Switch off the appliance with the ON/OFF switch (. No appliance fault. 10 Appliance interior . ■ This appliance is intended for use up to a maximum altitude of 4000 metres above sea level. en Utensils 18 Adjust the height of the etagere as follows: 1. To activate the interior lighting, press the ON/OFF switch (.If the door is open for longer than 60 minutes, the light will switch off automatically. Water stains on plastic parts. 11 Overview of menu. Siphon connection still sealed. Use a more intensive programme (more water changes). 2. Scoop out water, use a sponge if required. The interior light 1" comes on when the door is opened irrespective of whether the ON/OFF switch ( is switched on or off.When the door is closed, the light is off. Pull the catch of the child-proof lock towards yourself (1). ■ Use the dishwasher only in the home and only for its designated purpose: for washing domestic dishes. \* Not a fault! See turboSpeed 20 min. ■ Observe the safety instructions and the instructions for use on the machine cleaning detergent packaging. Loosen fastening screws for the furniture parts. ■ Inlet rate: minimum

10 litres/minute
■ Water temperature: cold water.
Make redundant connections to prevent accidents.
■ Utensils which are soiled with ash, wax, lubricating grease or ink.
AquaSensor\*
AquaSensor\* depending on the features of your dishwasher
The Aqua sensor is an optical measuring device (light barrier) which measures the turbidity of the rinsing water. Engage etagers.
No effect on appliance function.
Plastic parts inside the appliance may become discoloured during the service life of the dishwasher.
Spray arms
Limescale and contaminants in the rinsing water may block nozzles and bearings on the spray arms 1. and 1J.
Cover "clicks" into position.
In order to remove deposits, your dishwasher automatically changes the running of the programme (such as by increasing the cleaning temperature) at certain intervals.
19 Adjusting the height of the basket.
21 Adding detergent.
\*Getting to know your appliance
GettingtoknowyourapplianceDiagrams of the control panel and the interior of the appliance can be found at the front of the manual.
This will prevent steam from escaping and causing long-term damage to your built-in furniture.
Inlet rate: minimum 10 litres/minute
Water temperature: cold water.
This may cause small water stains.
■ If you switch from combined detergents to solo detergents, ensure that the water softening system and amount of rinse aid have been set to the correct value.
The Eco 50° programme is a particularly environmentally friendly programme.
Undo the waste water and drinking water connection.
Unusual foam formation.
Fold down the spikes as follows:
1. The LEDs go out.
~ Page 2 \* depending on the features of your dishwasher
Overview of menu
The dishwasher has been preset with certain settings for your convenience.
■ If you cannot obtain any information from the manufacturer, you must not install the dishwasher above or below these appliances.
Detergent dispenser cover 9° blocked by the tablet.
Too low rinsing temperature.
18 Unloading the dishwasher.
Recommended programme
Eco 50°
Coloured (blue, yellow, brown), difficult to remove to non-removable coatings in the appliance or on stainless steel utensils.
Switch on the ON/OFF switch (.
Spray arm rotation obstructed.
Knocking or rattling noise.
Turn off water supply, disconnect supply hose and drain water.
Remove overflowed rinse aid with a cloth.
Cover on the waste water pump loose.
Remaining running time display
When the programme is selected, the remaining programme time is indicated in the display window ).
5 Installation and connection
InstallationandconnectionThe dishwasher must be connected correctly, otherwise it will not function properly.
Do not cut through the supply hose.
Detergent dispenser cover must not be obstructed by utensils.
■ After installing the appliance, ensure that the plug is easily accessible.
34 4 Customer service
Four detergent into the dry detergent dispenser only.
Use different combination detergent with better drying performance.
Combination detergents function only up to a specific degree of hardness (usually 21°dH).
\*Depending on the features of your dishwasher
If you should find deposits in the interior of the dishwasher in spite of this, remove these deposits as follows:
1. CLICK &/&.
& Energy Save \* EnergySaveThe "Energy Save" function can be used to reduce water and energy consumption.
Keep pressing the timer programming button @ - or + until the desired time is displayed.
Disconnect appliance from the power supply; pull out the mains plug or switch off the fuse.
Too little or unsuitable detergent.
Safety features include an anti-snag lower guard and electronic blade stop.
Overview of programmes en 23 /Overview of programmes
OverviewofprogrammesThe max.
These will disappear after the first wash cycle.
■ Water pressure: at least 0.05 MPa (0.5 bar), maximum 1 MPa (10 bar).
Tablets used in the quick or short programme.
The rinse aid refill indicator h is switched off.
■ Install and connect the appliance according to the installation and assembly instructions.
~ "Electrical connection" on page 46
■ For some models: The plastic housing on the water connection contains an electric valve.
Salt content in the rinsing water too high, as salt dispenser lock not fastened firmly or salt was spilled while being refilled.
33 Waste water pump.
Caution!
Detergent will destroy the water softening unit!
Never pour detergent into the dispenser for special salt.
25 Save time (VarioSpeedPlus) .
Check for leaks.
Call customer service and quote the fault code.
en 37 Food remnants on the utensils.
in the chapter "Overview of programmes".
Glasses not dishwasher-proof, only suitable for dishwasher.
en 3 Table of contents enInstructionmanual 8 Intended use
■ Regularly wipe the door seals using a damp cloth and a little washing-up liquid.
25 Half load .
Here's how to set up the amount of added salt:
1. Deactivate childproof lock.
Please note the system will function only when the power supply is connected.
17 Cutlery drawer .
Change detergent brand.
Sensor does not detect salt tablets.
Clean pump and lock cover correctly.
~ "Waste water pump" on page 33
Fault code "f" is lit.
Filter in the water supply blocked.
Do not switch on a damaged appliance, but contact your supplier.
Film formation consisting of ingredients from food remnants and substances from the tap water (limescale), "soapy"
Check function of the water softening system (refill with salt) or, if using combined detergents (tablets), activate water softening system.
Appliance stops in the programme or programme is interrupted.
Ensure that both sides of the upper basket are at the same height.
18 Knife rack .
Damage
■ The appliance may be repaired and opened up by a technician only.
3. Control panel
See Fig.
■ Do not install the appliance near heat sources (radiators, heat storage tanks, cookers or other appliances which generate heat) and do not install under a hob.
The delay timer has been activated.
' Hot water \* '<<< '<<< '<<< / Off
The dishwasher can be connected to either hot (40-60°C) or cold water (